

ATRA® Speed Stake GEOWEB® Geocell Anchor

One-Piece Polymer Molded Anchors.

ATRA® Speed Stakes are engineered to provide maximum anchorage and resistance to sliding and uplift forces.

Designed for use with GEOWEB geocells for crest, toe, and internal anchoring (with or without tendons), ATRA Speed Stakes are extremely fast to install, deliver a strong holding force and are highly resistant to corrosive environments.



Fast, Efficient Anchors

- One piece unit requires no assembly. No bending of rebar, attaching ATRA clips to rebar, or sourcing rebar elsewhere.
- Lighter than comparable rebar anchors results in lower freight cost and easier handling on site.
- Pointed anchor tip easily punctures through geotextile underlayer better than rebar stakes for faster installation.
- Can be driven with pneumatic Hilti® or SDS-compatible drivers for fastest, lowest-impact driving.



Design & Performance

- Barbs and engineered stake shape adds increased level of holding force.
ATRA Speed Stake Equivalence:
 - 16-inch \geq 18-inch rebar anchor
 - 20-inch \geq 24-inch rebar anchor
- Specially engineered polymer blend material for highest strength and durability.
- Corrosion resistant, non-metallic anchors suitable for use in acidic soils, saltwater applications or where extended design-life is required.
- Flat polymeric head eliminates tire punctures on load support applications where permanent anchors are required (vs. rebar solutions).

FIND US | FOLLOW US

We are a global business with accessibility through a worldwide distribution network.



670 N Perkins Street • Appleton, Wisconsin, USA
800-548-3424 or +1 920-738-1328
Email: info@prestogeo.com • www.prestogeo.com